



NO SCALE

MINIMUM PAVEMENT DESIGN:

BITUMINOUS SURFACE COURSE: 1 1/2" S 9.5B
 INTERMEDIATE COURSE: 2 1/2" I 19.0B
 BASE COURSE: 8" ABC

STREET FEATURES:

FLEXIBLE STREET DESIGN
 COORDINATE STREET DESIGN ELEMENTS WITH TOWN STAFF
 STREET WIDTH OF 20 FT. FOR ONE-WAY
 STREET WIDTH OF 31 FT. FOR TWO-WAY
 CURB & GUTTER
 INFORMAL PARKING – ONE SIDE ONLY
 PARKWAY – 6 FT. ON EACH SIDE
 SIDEWALK – 5 FT. ON EACH SIDE
 UTILITY STRIP – 0.5 FT. ON EACH SIDE
 REQUIRES 47 FT. OF RIGHT-OF-WAY FOR ONE-WAY
 REQUIRES 54 FT. OF RIGHT-OF-WAY FOR TWO-WAY
 UTILITY LOCATION UNDERGROUND
 AVERAGE SPEED 20 MPH
 STREET TREES LOCATED IN PARKWAY

REVISIONS	
DATE	DESCRIPTION

TOWN OF KNIGHTDALE
 STANDARD DETAILS

LOCAL STREET - 2 LANES
 SIDEWALKS

STD. NO.

3.02-1