



NO SCALE

**MINIMUM PAVEMENT DESIGN:**

BITUMINOUS SURFACE COURSE: 1 1/2" S 9.5B  
 INTERMEDIATE COURSE: 2 1/2" I 19.0B  
 BASE COURSE: 8" ABC

**STREET FEATURES:**

FLEXIBLE STREET DESIGN  
 COORDINATE STREET DESIGN ELEMENTS WITH TOWN STAFF  
 TRAVEL LANES OF 10 FT.  
 CURB & GUTTER  
 STRIPED PARALLEL PARKING – ONE SIDE ONLY  
 PARKWAY – 6 FT. ON ONE SIDE  
 SIDEWALK – 6 FT. ON PARKING SIDE; 5 FT. ON OPPOSING SIDE  
 REQUIRES 54 FT. OF RIGHT-OF-WAY  
 UTILITY LOCATION UNDERGROUND  
 AVERAGE SPEED 20 MPH  
 STREET TREES LOCATED IN PARKWAY  
 STREET TREES LOCATED ON PARKING SIDE OF STREET  
 WILL BE PLACED IN CURB BULB OUT OR BACK OF SIDEWALK

REVISIONS	
DATE	DESCRIPTION

TOWN OF KNIGHTDALE  
 STANDARD DETAILS

LOCAL STREET - ON STREET PARKING  
 ONE SIDE ONLY

STD. NO.

3.02-2