



NO SCALE

MINIMUM PAVEMENT DESIGN:

BITUMINOUS SURFACE COURSE: 1 1/2" S 9.5B
 INTERMEDIATE COURSE: 2 1/2" I 19.0B
 BASE COURSE: 8" ABC

STREET FEATURES:

TRAVEL LANES OF 10 FT.
 CURB & GUTTER
 STRIPED PARALLEL PARKING
 PARKWAY — 5 FT. ON EACH SIDE
 SIDEWALKS — 5 FT. ON EACH SIDE
 UTILITY LOCATION UNDERGROUND OR ALLEY
 STREET TREES LOCATED IN PARKWAY
 UTILITY LOCATION BEHIND CURB ON NCDOT FACILITIES
 BICYCLE FACILITY PAVEMENT MARKINGS SHALL ADHERE TO MUTCD STANDARDS
 AVERAGE SPEED 20–25 MPH
 PROVIDE ELEMENTS PER URBAN STREETSCAPE DESIGN FEATURES DETAIL

REVISIONS	
DATE	DESCRIPTION

TOWN OF KNIGHTDALE
 STANDARD DETAILS

URBAN MAIN STREET - 2 LANES
 SEPARATED BIKE LANES (ABOVE THE CURB)

STD. NO.

3.04-1