



NO SCALE

MINIMUM PAVEMENT DESIGN:

BITUMINOUS SURFACE COURSE: 1 1/2" S 9.5B
 INTERMEDIATE COURSE: 2 1/2" I 19.0B
 BASE COURSE: 8" ABC

STREET FEATURES:

TRAVEL LANES OF 11 FT.
 STREET PARKING OF 8.5 FT. FROM FACE OF CURB
 CURB & GUTTER
 STRIPED PARALLEL PARKING
 PARKWAY – 6 FT. ON EACH SIDE
 WIDE SIDEWALK – 10 FT. ON EACH SIDE
 REQUIRES 80 FT. OF RIGHT-OF-WAY
 UTILITY LOCATION UNDERGROUND OR ALLEY
 AVERAGE SPEED 20–25 MPH
 STREET TREES LOCATED IN PARKWAY
 UTILITY LOCATION BEHIND CURB ON NCDOT FACILITIES
 PROVIDE ELEMENTS PER URBAN STREETScape DESIGN
 FEATURES DETAIL

REVISIONS	
DATE	DESCRIPTION

TOWN OF KNIGHTDALE
 STANDARD DETAILS

URBAN AVENUE - 2 LANES
 WIDE SIDEWALK

STD. NO.
 3.06-1